

EZStation Video Management Software



Key Features

- Unified management for IP cameras, NVRs, decoding devices, and etc.
- Up to 256 local channels and 128 cloud channels; add, edit and share cloud devices.
- Automatic device discovery (or search by network segment); add devices by domain name/IP address; add devices and adjust time in batch.
- Diverse capabilities:
 - Live view: up to 64 live view, scene, custom view, split screen, multi-window display, corridor mode, sequence display, audio, two-way audio
 - Recording: local recording, recording schedule, alarm-triggered recording, recording download
 - Playback: recording search by time/event, local/remote playback, synchronous playback, smart search, and play recordings on SD card
 - PTZ control: Pan, tilt, zoom, 3D positioning, preset, patrol, pattern, and patrol plan
 - Alarm: temperature, device online/offline, motion detection, and VCA alarming and alarm triggered live view and recording

- People counting: entered/left/entered and left statistics, daily/weekly/monthly/yearly report export.
- E-Map: hot spot for easy live view, hot zone for sub-map, eagle eye, and map alarming
- Video wall: decoding channel configuration, sequence display and playback on video wall
- Flexible maintenance such as log export, alarm info export
- Friendly user interface for easy operation

Specifications

| Function | Description |
|--|---|
| Note: Functions and system requirements may vary with software version. | |
| Device Management | |
| Devices Supported | Max. 256 local channels and 128 cloud channels |
| | Max. 64 local devices and 64 cloud devices |
| Features | Auto device discovery, and adding, configuring, time adjusting in batch |
| Live Monitoring | |
| Screen Layout | 1/ 4/ 5 /6 /8 /9 /10 /13 /16 /17 /25 /32 /36 /64 split screen(s) with up to 3 sub screens Note: Max. 64 screens live view |
| PTZ Control | Pan, Tilt, Zoom, Preset, Patrol, 3D positioning, IR control, wiper control, heat control, snow removing Note: Actual functionality may vary depending on device capability. |
| Features | Sequence display, snapshot, local record, audio, two-way talk, and instant playback |
| Playback | |
| Video Source | Recording video from NVR |
| Max Channels | 16 (Async)/16 (Sync) |
| Search Type | Time/event/calendar |
| Export File | .ts, .mp4 |
| Features | Recording schedule and download, snapshot, -16x~16x speed for forward and backward, audio, digital zoom |
| Alarm | |
| Type | Multiple alarm types including device alarms and VCA alarms |
| Alarm Triggering | Live view, recording, email, preset, alarm output and etc. |
| Features | Alarm schedule, actions setup, alarm memo, alarm info popup |
| E-Map | |
| Format | PNG/JPEG/BMP |
| Map Alarm | Alarm flash, search and acknowledge |
| Features | Hot spot, hot zone, map zoom in/out, eagle eye |
| System Requirement | |
| EZStation 64-bit | Operating System: Microsoft Windows 7/Windows 8/Windows10 (64-bit) CPU: Intel Core i5 3.1 GHz or higher Memory: 4GB or higher |
| EZStation 32-bit | Operating System: Microsoft Windows 7/Windows 8/Windows10 (32-bit or 64-bit) CPU: Intel Pentium IV 3.0 GHZ or higher (4 Core, 3.0GHZ recommended) Memory: 2GB or higher Note: The 64-bit Windows shall be able to host 32-bit software. |

| | |
|---------------|--|
| EZStation Mac | <p>Operating System: Mac OS 10.11 or higher</p> <p>CPU: Intel Core i5 3.1 GHz or higher</p> <p>Memory: 4GB or higher</p> |
|---------------|--|

Zhejiang Uniview Technologies Co., Ltd.

South Tower, Building 10, Wanlun Science Park, 88 Jiangling Road, Hangzhou, P.R. China 310051

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2011-2018 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.